

Color Options

- Black
- White

Standard Features

- Single boiler system
- 4 programmable volumetric dosing touch pads
- Turn style steam knobs
- Raised groups
- Double scale manometre for displaying the boiler and pump pressure



	1 Group 	2 Group 	2 Group 	3 Group 
Total Wattage	2,330 watt	2,930 watt	4,800 watt	5,350 watt
Boilers	6 L	10.5 L	10.5 L	17 L
Net Weight	130 lbs	159 lbs	159 lbs	194 lbs
Approx Ship Weight	172 lbs	216 lbs	216 lbs	285 lbs
Measurements W x D x H	22 x 22 x 21.3	30.3 x 22 x 21.3	30.3 x 22 x 21.3	39.8 x 22 x 21.3
Power	120 volt / 19.42 A	120 V / 24.42 A	230 V / 20.9 A	230 volt / 23.26 A
	 NEMA 5-20P	 NEMA 5-30P	 Nema L6-30	 Nema L6-30

Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50ppm.
- Water softener must be installed if it exceeds the limits.
- Minimum incoming water flow rate of 35 GPH and the maximum line pressure of 70 PSI/5 BAR

Drain Requirements

Open gravity drain of minimum 1.25 inch within 4 feet of the machine

*Updated 10/2025

